

Termiglass

Accessories FACT SHEET

'Quickstrip Strip Shielding'

Ensures faults in render, brickwork or masonry are protected against concealed termite entry. Grooved for optimum bond to mortar, cement and construction adhesives. Excess material easily removed along a groove to give a uniform surface finish - no need for cutting.

Specifications: High Flex PVC

'Frizbee' Collar

Patent protected collar seals out termites at electrical, plumbing, gas, telephone and other service penetrations. Resistance fitting ensures termite barrier integrity when there is movement of ground/slab (Reactive soils).

Specifications:

Toughened Polypropylene
Sizes - < 40mm, 50mm, 80mm
100mm and multi-fit penetrations

Approvals and Compliance:

Complies with BCA 96
Complies with AS 3660.1-2000
"Termite management - New building work"
Appraisal - CSIRO Technical Assessment number 302

Termicide Sealant

Termite resistant silicone sealant. Suitable for sealing between other termite resistant materials, saw cuts, shrinkage cracks, footing and slab edge rebates, ant capping, cold joints, key joints and control joints. Termicide Sealant can stretch up to 630% before breaking.

Approvals and Compliance:

Complies with BCA 96
Complies with AS 3660.1-2000
"Termite management - New building work"
Appraisal - CSIRO Technical Assessment number 299

Termicide Sealant WM

Patent protected termite resistant sealing compound

Specifications: UV Stabilized

Temperature range -50°C to +150°C

Approvals and Compliance:

Complies with BCA 96
Complies with AS 3660.1-2000
"Termite management - New building work"
Appraisal - CSIRO Technical Assessment number 302